

Data Sheet

Fujitsu PRIMERGY RX100 S6 Mono socket 1 U rack server

Cost optimized and highly modular multi usage rack server

The PRIMERGY RX Rack Server family is the perfect platform to form dynamic infrastructures for your business processes today and in the coming decade. You will thus benefit several times over from our recognized experience in optimized data center technology and our innovative strength in developing energy-efficient and cost/performance-optimized rack systems for universal use. PRIMERGY rack servers, built upon industry standards, focus from a functional viewpoint on core features: energy efficiency, reliability, optimized for virtualization, ease of operation and maintenance, flexibility for your future. And thus they notably meet your requirements for outstanding cost efficiency. Optimal operating costs and long-term usability comply with the IT quality required by your customers. Our responsibility goes way beyond the hardware as our tailor-made service packages mean that you can rely on the best support for your IT during its whole lifecycle.

PRIMERGY RX100 S6

Data centers are increasingly seeking platform solutions that have minimal impact on their budgets and are easy to implement and run. PRIMERGY RX100 S6 is the right answer. The RX100 S6 meets the needs of business applications with its technical developments, such as Quad-Core Intel® Xeon® processor 3400 series and the new Dual-Core Intel® Core™ i3 processor, integrated RAID 0/1/5/6 and a memory of up to 32 GB. It unites the advantages of low-cost SATA or SAS/SSD hard disk technology with a space-saving 1U chassis and a depth of less than 60 cm. Integrated network and management functions together with the latest power saving technologies make the system ideal for infrastructure solutions for customers with limited budgets.



Features and Benefits

| Main Features | Benefits |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Flexibility</p> <ul style="list-style-type: none"> ■ 2x 3.5" SATA or SAS HDDs or 4x 2.5" SATA/SAS/SSD HDDs, all hot-plug with modular RAID controllers from low-entry embedded SATA RAID 0, 1; entry SAS 1.0 RAID 0, 1; newest SAS 2.0 RAID 0, 1 to performant SAS 2.0 RAID 5,6 controller | <ul style="list-style-type: none"> ■ Highly modular platform for all purposes that can be tailored exactly to customer requirements ■ More tasks are handled in less time. More efficient work is possible in your IT sector and less power consumption too. Quad-Core Xeon® provides significant performance/watt growth ■ Enough memory even for databases or virtualization tasks ■ Get the best performance but save energy and protect the environment ■ Top-speed communications link via LAN as standard ensures continuity in failover mode ■ Better serviceability and accessibility for low-entry rack environments ■ Have all the systems important informations handy in a second |
| <p>New platform</p> <ul style="list-style-type: none"> ■ Quad-Core Intel® Xeon® processor 3400 series with virtualization technology, and the new Intel® Core™ i3 processor series generation of Intel® Dual-Core CPUs with very low power consumption ■ Up to 32 GB of RAM - new dimensions for the mono socket server | |
| <p>Energy efficiency</p> <ul style="list-style-type: none"> ■ Low voltage Intel® Xeon® processors and new enhanced power supply with CSCI Silver certification and improved system energy features powered by iRMC S2 | |
| <p>Reliability</p> <ul style="list-style-type: none"> ■ 2 x Gbit/s Ethernet LAN with TCP/IP accelerator plus switchable Service LAN (dedicated or shared) | |
| <p>Serviceability</p> <ul style="list-style-type: none"> ■ Customer Self Service Module or front VGA + USB 2.0 as option | |
| <ul style="list-style-type: none"> ■ System ID card with complete system information, e.g. Model, Serial Number, MAC Adresses etc. | |

Technical details

| | | |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| PRIMERGY RX100 S6 | | |
| Housing type | Rack | Rack |
| Hard disk architecture | 3.5" SAS/SATA | 2.5" SAS/SATA |
| Power supply | Standard | Standard |
| Mainboard | | |
| Mainboard type | D 2863 | |
| Chipset | Intel® 3420 | |
| Processor quantity and type | 1 x Intel® Core™ i3 processor / Intel® Celeron® processor / Intel® Pentium® Dual-Core processor / Intel® Xeon® processor 3400 series | |
| Processor | | |
| | Intel® Celeron® processor G1101 (2C, 2.26 GHz, TLC: 2 MB, Turbo: No, 1066 MHz, 73 W) | |
| | Intel® Core™ i3-540 processor (2C/4T, 3.06 GHz, TLC: 4 MB, Turbo: No, 1333 MHz, 73 W) | |
| | Intel® Core™ i3-550 processor (2C/4T, 3.20 GHz, TLC: 4 MB, Turbo: No, 1333 MHz, 73 W) | |
| | Intel® Pentium® processor G6950 (2C, 2.80 GHz, TLC: 3 MB, Turbo: No, 1066 MHz, 73 W) | |
| | Intel® Xeon® processor L3406 (2C/4T, 2.26 GHz, TLC: 4 MB, Turbo: 2/2, 1066 MHz, 30 W) | |
| | Intel® Xeon® processor L3426 (4C/8T, 1.86 GHz, TLC: 8 MB, Turbo: 2/2/9/10, 1333 MHz, 45 W) | |
| | Intel® Xeon® processor X3430 (4C/4T, 2.40 GHz, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W) | |
| | Intel® Xeon® processor X3450 (4C/8T, 2.66 GHz, TLC: 8 MB, Turbo: 1/1/4/4, 1333 MHz, 95 W) | |
| | Intel® Xeon® processor X3470 (4C/8T, 2.93 GHz, TLC: 8 MB, Turbo: 2/2/4/5, 1333 MHz, 95 W) | |
| | Intel® Xeon® processor X3480 (4C/8T, 3.06 GHz, TLC: 8 MB, Turbo: 2/2/4/5, 1333 MHz, 95 W) | |
| Memory slots | 4 (2 banks with 2 DIMMs each) | |
| Memory slot type | DIMM (DDR3) | |
| Memory capacity (min. - max.) | 1 GB - 32 GB | |
| Memory protection | Advanced ECC | |
| Memory notes | Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. | |
| Memory modules | | |
| | 1 GB (1 module(s) 1 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM | |
| | 2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM | |
| | 4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM | |
| | 4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM | |
| | 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM | |
| | 8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM | |
| Memory modules notes | Unbuffered / Registered | |
| Interfaces | | |
| USB ports | 8 x (2x (+1x optional) front, 4x back, 1x internal planned for VMWare) | |
| Graphics (15-pin) | 1 x VGA (15-pin) | |
| Serial connection | 1 x serial RS-232-C, usable for iRMC or system or shared | |
| LAN / Ethernet (RJ-45) | 2 x Gbit/s Ethernet | |

Interfaces

| | |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Service LAN (RJ45) | 1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------|

Onboard or integrated Controller

| | |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RAID Controller | Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (option, occupies one PCIe slot). See under Components RAID controller |
| SATA Controller | Intel® 3420 Ixex Peak PCH Platform Control Hub, 1 port used for accessible drive 4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux; |
| LAN Controller | Intel® 82574 + Intel® 82578 onboard, 2 x 10/100/1000 Mbit/s Ethernet (TCP/IP acceleration), PXE-Boot via LAN from PXE server, iSCSI Boot (also diskless) via onboard LAN |
| Remote Management Controller | Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible |
| Trusted Platform Module (TPM) | optional TPM |

Onboard or integrated Controller (Base unit specific)

| | | |
|-----------------------------------|------------------------------------|------------------------------------|
| RAID Controller | 4 port SATA with RAID 0/1 for HDDs | 4 port SATA with RAID 0/1 for HDDs |
| SATA Controller | 4-port SATA 3GB with RAID 0, 1 | 4-port SATA 3Gb with RAID 0, 1 |
| SATA Controller type notes | for hot-plug SATA hard disks | for hot-plug SATA hard disks |

Slots

| | |
|--------------------------------------|---------------------------------------------------------------------|
| PCI-Express 2.0 x4 (mech. x8) | 1 x (for Modular RAID only) |
| PCI-Express 2.0 x8 | 2 x low profile (one of these can be used as standard short, 175mm) |

Drive bays

| | |
|------------------------------|---------------------------------------------------------------------------------------------------------------|
| Accessible drive bays | 1 x 5.25/0.5-inch for CD-RW/DVD 1 x 3.5/0.5-inch for ServerView Local Service Panel or front VGA + USB 2.0 |
|------------------------------|---------------------------------------------------------------------------------------------------------------|

Drive bays (Base unit specific)

| | | |
|-----------------------|--------------------------------|--------------------------------|
| Hard disk bays | 2 x 3.5-inch hot-plug SAS/SATA | 4 x 2.5-inch hot-plug SAS/SATA |
|-----------------------|--------------------------------|--------------------------------|

Operating panel

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating buttons | On/off switch NMI button |
| Status LEDs | System status (amber / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (amber / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow) |
| Service display | Optional: ServerView Local Service Panel (LSP) |

BIOS

| | |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BIOS features | ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | |
|-----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certified or supported operating systems and virtualization software | Microsoft® Windows Server® 2008 R2 (containing Hyper-V) Microsoft® Windows Server® 2008 Microsoft® Windows Server® 2003 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux VMware vSphere 4.1 |
| Operating system release link | http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421 |
| Operating system notes | VMware ESX hints: - SATA RAID is not supported - Storing virtual machines locally requires a SAS RAID Controller - Onboard GbE is supported on one of the two ports Support of other Linux derivatives on demand |

Server Management

| | |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Standard | ASR&R Automatic Server Recovery and Restart PDA Prefailure Detection and Analysis |
| Option | ServerView Integration for Tivoli TEC®, Tivoli NetView, HP NNM and HP Operations Manager iRMC S2 Advanced Pack |
| Server Management notes | Regarding Operating System dependencies for ServerView Suite Software Products see dedicated Product Data sheets. |

Dimensions / Weight

| | |
|----------------------------------|---------------------------------------------------|
| Rack (W x D x H) | 482.6 mm (Bezel) / 431mm (Body) x 557 x 42.5 mm |
| Mounting Depth Rack | 557 mm |
| Height Unit Rack | 1 U |
| Mounting Cable depth rack | 200 mm cable depth |
| Weight | up to 14 kg |
| Weight notes | Actual weight may vary depending on configuration |
| Rack integration kit | Rack integration kit as option |

Environmental

| | |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Noise emission | Measured according to ISO 7779 and declared according to ISO 9296 |
| Sound pressure (LpAm) | w/o PCIe cards 27.6 dB(A) (idle)/27.6 dB(A) (op.) / w/ PCIe cards 35.8 dB(A) (idle)/40.7 dB(A) (op.) |
| Sound power (LWAd; 1B = 10dB) | System w/o PCIe cards 4.4 B (idle)/4.3 B (operating) / w/ PCIe cards 5.2 B (idle)/ 5.7 B (operating) |
| Operating ambient temperature | 15 - 35°C |
| Operating environment | FTS 04230 - Guideline for Data Center (installation locations) |
| Operating environment Link | http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe |

Electrical values

| | |
|--------------------------------------------|-------------------------------|
| Power supply configuration | 1x standard power supply |
| Standard power supply output | 350 W |
| Rated voltage range | 100 V - 127 V / 200 V - 240 V |
| Rated frequency range | 47 Hz - 63 Hz |
| Rated current max. | 6 A |
| Active power (max. configuration) | 288 W |
| Apparent power (max. configuration) | 293 VA |
| Heat emission | 1036.8 kJ/h (982.7 BTU/h) |

Energy Star® 1.0 certified configurations

The following products use less energy and reduce greenhouse gas emissions by meeting the strict Energy Star guidelines.

PRIMERGY RX100 S6 E-StarFam1 (Dual-Core CPUs)
PRIMERGY RX100 S6 E-StarFam2 (Quad-Core CPUs)



http://ts.fujitsu.com/products/standard_servers/e_efficient.html

Compliance

| | |
|----------------|----|
| Germany | GS |
|----------------|----|

| Compliance | |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Europe | CE Class A * |
| USA/Canada | CSAc/us ULc/us FCC Class A |
| Global | CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) |
| Japan | VCCI |
| China | CCC |
| Australia/New Zealand | C-Tick |
| Taiwan | BSMI |
| Compliance notes | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures. |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates/default.aspx |

Components

| | |
|--------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hard disk drives | SSD SATA, 3 Gb/s, 64 GB, SLC, hot-plug, 2.5-inch, enterprise |
| | SSD SATA, 3 Gb/s, 32 GB, SLC, hot-plug, 2.5-inch, enterprise |
| | HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical |
| | HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical |
| | HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, hot-plug, 2.5-inch, economic |
| | HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, business critical |
| | HDD SATA, 3 Gb/s, 160 GB, 7200 rpm, hot-plug, 3.5-inch, economic |
| | HDD SATA, 3 Gb/s, 160 GB, 7200 rpm, hot-plug, 2.5-inch, business critical |
| | HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, hot-plug, 2.5-inch, economic |
| | HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical |
| | HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical |
| | HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise |
| | HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise |
| | HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise |
| | HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise |
| | HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise |
| | HDD SAS, 6 Gb/s, 146 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise |
| HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise | |
| HDD SAS, 3 Gb/s, 146 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise | |
| Hard disk notes | One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software Mix of SAS and SATA HDD is possible but requires separate RAID sets and BC SATA drives |
| Optical drives | Blu-ray Disc™ Combo Drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I |
| SCSI / SAS Controller | SCSI Ctrl. 320 MB 1x int /1x ext SAS Ctrl. 6 Gb 8 ports ext. PCIe Gen2 x8 SAS Ctrl. 3 Gb 4 ports int. / 4 ports ext. |

| | |
|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| RAID Controller | RAID 5/6 Ctrl., HDD SAS 6 Gb, LSI , 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI SAS2108) |
| | Integrated RAID 5/6 Ctrl., HDD SAS 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI SAS2108) |
| | Integrated RAID 0/1 Ctrl., SAS/SATA 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, no BBU support (based on LSI SAS2008) |
| | Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gb, 4 ports int. RAID level: 0, 1, 1E, no BBU support , for internal SAS tapes (based on LSI 1064e) |
| LAN Controller | Converged Network Adapter 2 x 10 Gb Emulex OCe10102 |
| | Ethernet Ctrl. 1 x 1 Gb Intel® Gigabit CT Desktop Adapter |
| | Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PF Server Adapter |
| | Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PT Server Adapter |
| | Ethernet Ctrl. 2 x 10 Gb Intel® Ethernet Server Adapter X520-DA2 |
| | Ethernet Ctrl. 2 x 1 Gb Fujitsu Eth Ctrl 2x1Gbit PCIe x4 D2735 Cu |
| | Ethernet Ctrl. 2 x 1 Gb Intel® PRO/1000 PT Dual Port Server Adapter |
| | Ethernet Ctrl. 4 x 1 Gb Fujitsu Eth Ctrl 4x1Gbit PCIe x4 D2745 Cu |
| | Ethernet Ctrl. 4 x 1 Gb Intel® PRO/1000 PT Quad Port Server Adapter |
| Rack infrastructure | Cable Arm 1U for PRIMECENTER- and 3rd-party racks |
| | Rackmount kit full extraction (760mm), tool less mounting |
| | Rackmount kit partly extraction (524mm), tool less mounting |
| Warranty | |
| Standard Warranty | 1 year |
| Service level | On-site Service (depending on country) |
| Maintenance and Support Services - the perfect extension | |
| Recommended Service | 7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner. |
| Spare Parts availability | 5 years |
| Service Weblink | http://ts.fujitsu.com/Supportservice |

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY RX100 S6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY RX100 S6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/Primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU LIMITED
Mies-van-der-Rohe-Straße 8
80807 München
Germany
Website: www.ts.fujitsu.com
2010-12-10 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions